

ESPECIFICACIONES TECNICAS DE LUBRICANTES

NO.	REFERENCIA	TIPO/USO	IDENTIFICACION	DENCIDAD MINIMO	COLOR	TBN MINIMO	VISCOSIDAD MINIMO	IV MININO
1	ISO-68	HIDRÁULICO	ISO VG 68	0.87 a 0.89	N/A	50.6	74.8	90
2	15W-40	MOTOR	API CI-4	0.8705	ÁMBAR	13	15.6	130
3	20W-50	MOTOR	API SL	0.8705	ÁMBAR	13	19.1	160
4	10W-40	MOTOR	API SM	0.8705	ÁMBAR	13	15.6	130
5	ATF	TRANSM.AUTOMATIC.	DEX/MERCON	0.9500	ROJO	N/A	37.0	184
6	2-T	MOTOR 2-T	API TC	0.875	ÁMBAR	N/A	7.0	120
7	POWER STEERING	DIRECCIÓN HIDRÁULICA	ATF-D3	0.860	ROJO	10.5	7.6	187
8	LIQ. FRENO	SIST.DE FRENOS	DOT-4	1.0 a 1.4	AMARILLO	N/A	1.50	N/A
9	10W	HIDRÁULICO	CC/SC	0.8770	N/A	4	37.7	107
10	COOLANT VWG-12 PLUS	SIST. ENFRIAMIENTO	50% ELC50% AGUA PURIFICADA	N/A	ROJO FRESA	N/A	N/A	N/A
11	SOLUCIÓN	BATERÍA	N/A	N/A	N/A	N/A	N/A	N/A
12	AGUA DESTILADA	BATERÍA	N/A	N/A	N/A	N/A	N/A	N/A
13	DESGRASANTE	LAVADO PIEZAS MOTORES	N/A	N/A	N/A	N/A	N/A	N/A
14	SAE 50	TRANSM.EQUIPO PESADOS	API CI-4	0.9100	ÁMBAR	8.0	16.3	130

